

CP4L16



1.5 sq.mm Push in 4 level compact Terminal Blocks

4 level marshelling Terminal Block. The space saving method for potential and signal distribution. The push in technology for easy wiring connection i.e. the stripped wire is simply inserted into the terminal point.

TECHNICAL DATA

Rated Voltage	320 V
Rated Current	17.5 A

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	1.5 mm ²

DIMENSIONS

Height with DIN 35 x 15 mm rail	63.3 mm
Height with DIN 35 x 7.5 mm rail	55.8 mm
Length	73 mm
Width (Thickness)	9 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CP4L16	1.5 sq.mm 4 level Marshelling Terminal Block in Grey colour	10

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
--------	----------	-------------	-----------

	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50

	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50

	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
--	-------	---	----

	CA104	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
--	-------	---	----

	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	25
--	-------	--	----

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
--------	----------	-------------	-----------

	CA509/K3.5V	Marking Tag Blank suitable for separator plate of CP8L32 & CP8L32(I.S)	100
--	-------------	--	-----

	CA509/K9	Blank Marking Tag	100
--	----------	-------------------	-----

APPROVALS



NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

CP4L16



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	IEC/EN60947-7-1		
Conductor Cross Section Stranded min.	0.2 mm ²		
Conductor Cross Section Stranded max.	1.5 mm ²		
Rated Voltage	320 V		
Rated Current	17.5 A		