


CPDLKFT2.5 (I.S)



connectwell
THE RIGHT CONNECTION

2.5 sq.mm knife disconnecting Push in double level compact Terminal block.

CP series Push In type Terminal Block are the next generation, compact Terminal Blocks. The new CP series terminals have a much wider range for wire terminations. The Push button on the top is to be pressed for using flexible cable without lug for connections. Lugged cable can be directly pressed into clamp to make connections..Disconnection is achieved by opening the insulated knife (blade) contact in the middle of the terminal.

TECHNICAL DATA

Rated Voltage	500 V
Rated Current	16 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Knife Type Disconnect and Test
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Rated Surge Voltage	6 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	2.5 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	12 AWG
Stripping Length	10 mm

DIMENSIONS

Height with DIN 35 x 15 mm rail	57.5 mm
Height with DIN 35 x 7.5 mm rail	50 mm
Length	107.25 mm
Width (Thickness)	5 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CPDLKFT2.5(I.S)	2.5 sq.mm Knife Disconnecting Push in Terminal Block in Grey colour	100

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	CA104	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	JX2.5/2	Shorting Link for 2.5 sq mm series	100
	JX2.5/3	Shorting Link for 2.5 sq mm series	50
	JX2.5/4	Shorting Link for 2.5 sq mm series	50
	JX2.5/5	Shorting Link for 2.5 sq mm series	50
	JX2.5/6	Shorting Link for 2.5 sq mm series	50
	JX2.5/7	Shorting Link for 2.5 sq mm series	10
	JX2.5/8	Shorting Link for 2.5 sq mm series	10
	JX2.5/10	Shorting Link for 2.5 sq mm series	10
JX2.5/20	Shorting Link for 2.5 sq.mm series	10	
	CA509/K4	Blank Marking Tag	100
	MS5	Marking Tag Blank suitable for CXM2.5 / CXMG2.5 Terminal Blocks	100
	SCS0.5/3	Electricians Screwdriver for slotted screws	10
	EPCDLK2.5	End Plate	50


APPROVALS



NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

CPDLKFT2.5 (I.
S)



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	CSA C. 22. 2 No:158	IEC/EN60947-7-1
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm ²
Conductor Cross Section Stranded max.	12 AWG	12 AWG	2.5 mm ²
Rated Voltage	300 V	300 V	500 V
Rated Current	14 A	14 A	16 A