


CPF4L



**connectwell**  
THE RIGHT CONNECTION

4 sq.mm push in Fuse compact Terminal Blocks

CP series Push-In Terminal Blocks have a specialised connection system that enables tool less wire connections. Reliable, vibration resistant, gas tight connections are made with inbuilt high quality stainless steel Push in spring clamps.

**TECHNICAL DATA**

Rated Voltage	1000 V
Rated Current	10 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Single Level Fuse with Indication
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Rated Surge Voltage	4 KV
Pollution Degree	3

**CONNECTION DATA**

Conductor Cross Section Stranded min.	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded max.	4 mm <sup>2</sup>
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	10 AWG
Stripping Length	10 mm

**DIMENSIONS**

Height with DIN 35 x 15 mm rail	76.3 mm
Height with DIN 35 x 7.5 mm rail	68.8 mm
Length	54.8 mm
Width (Thickness)	6 mm

**FUSE SPECIFICATIONS**

Fuse Type	Glass type fuse
Fuse Size	5 X 20 mm

**ORDERING INFORMATION**

CAT. NO.	DESCRIPTION	STD. PACK
CPF4L6-60V	4mm <sup>2</sup> Ø5X20mm PUSH IN FUSE TB 6-60V	50
CPF4L110-240V	4mm <sup>2</sup> Ø5X20mm PUSH IN FUSE TB110-240V	50

**ACCESSORIES**

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50

**ACCESSORIES**

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	PPCX4/3	Partition Plate in Grey colour	50
	PPCX4/3O	Partition Plate in Orange colour	50
	JX4/2	Shorting Link for 6 mm wide TB	100
	JX4/3	Shorting Link for 6 mm wide TB	50
	JX4/4	Shorting Link for 6 mm wide TB	50
	JX4/5	Shorting Link for 6 mm wide TB	50
	JX4/8	Shorting Link for 6 mm wide TB	10
	JX4/10	Shorting Link for 6 mm wide TB	10
JX4/16	Shorting Link for 6 mm wide TB	10	
	CA509/K6	Blank Marking Tag	100
	MC6	MARKER CARD 6MM PITCH WITH 72 TAGS	10


**APPROVALS**



**NOTES**

The Rated current is with the use of copper (Cu) conductor/Wire

CPF4L



**connectwell**  
THE RIGHT CONNECTION

**RATINGS AS PER STANDARDS**

<b>STANDARDS</b>	<b>UL 1059</b>	<b>CSA C.22.2 No:158</b>	<b>IEC/EN60947-7-3</b>
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded max.	10 AWG	10 AWG	4 mm <sup>2</sup>
Rated Voltage	600 V	600 V	1000 V
Rated Current	10 A	10 A	10 A