

# CSST10



120 sq.mm Single Stud Type Terminal Block.

These Terminal Blocks are preferred for applications where the connections are subjected to severe vibrations. The wire is crimped to ring type Lug and connected to the Stud Terminal Block. The CSST10 Terminal Blocks suitable for wire sizes from 10 to 120 sq.mm. The self locking nut can then be fastened to complete the connection.

### TECHNICAL DATA

Weight	65 gms
Rated Voltage	800 V
Rated Current	269 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Feed Through
Mounting Possibility	DIN 35/DIN 35-15 Rail
Stud Size	M10 x 31.5

### CONNECTION DATA

Conductor Cross Section Stranded min.	10 mm <sup>2</sup>
Conductor Cross Section Stranded max.	120 mm <sup>2</sup>

### DIMENSIONS

Height with DIN 35 x 15 mm rail	63.3 mm
Height with DIN 35 x 7.5 mm rail	55.8 mm
Length	50 mm
Width (Thickness)	31.2 mm

### ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CSST10	120 sq.mm Single Stud Type Terminal Block in Grey colour	10

### ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA509/K8	Marking Tag with Vertical printing.	100
	CSSTPC	Protective Cover	10

### ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CSSTSP	spacer plate in grey color	30
	SPCSST2	partition plate in grey color	50
	SPCSST4	Protective Cover Holding Plate	50
	MC8	MARKER CARD 8MM PITCH WITH 48 TAGS	10

### NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

CSST10



**connectwell**  
THE RIGHT CONNECTION

**RATINGS AS PER STANDARDS**

<b>STANDARDS</b>	<b>IEC 60947-7-1</b>		
Conductor Cross Section Stranded min.	10 mm <sup>2</sup>		
Conductor Cross Section Stranded max.	120 mm <sup>2</sup>		
Rated Voltage	800 V		
Rated Current	269 A		
Tightening Torque	10 Nm		