

Object reference not set to an instance of an object.

CSST6H12

35 sq.mm Single Stud Type Terminal Block with Horizontal Tab connection

These Terminal Blocks are preferred for applications where the connections are subjected to severe vibrations. The wire is crimped to ring type Lug and connected to the Stud Terminal Block. Terminal Blocks suitable for wire sizes from 2.5 to 35 sq.mm The self locking nut can then be fastened to complete the connection.

TECHNICAL DATA

Rated Voltage	500 V
Rated Current	115 A
Tightening Torque	5.3 Nm
Housing Material	Polyamide
Standard Colour	Grey
Product Function	Feed Through
Mounting Possibility	DIN 35/DIN 35-15 Rail
Stud Size	M6 x 31.5

CONNECTION DATA

Conductor Cross Section Stranded min.	2.5 mm ²
Conductor Cross Section Stranded max.	35 mm ²





DIMENSIONS

Height	53.7 mm
Length	50 mm
Width (Thickness)	22 mm





ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CSST6H12	35 sq.mm Single Stud Type Terminal Block with Horizontal Tab connection	10

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CSSTPC	Protective Cover	10
	CSSTSP	spacer plate in grey color	30

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	SPCSST2	partition plate in grey color	50
	SPCSST4	Protective Cover Holding Plate	50
	MC8	MARKER CARD 8MM PITCH WITH 48 TAGS	10
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	25

NOTES

The Rated current is with the use of copper (Cu) conductor/Wire