

CSTDE



connectwell
THE RIGHT CONNECTION

6 sq.mm Stud Type Diode Terminal with Heat Sink

CSTDE Terminal blocks are preferred for applications where the connections are subjected to severe vibrations. These Terminal Blocks are suitable for screw and solder diodes type SKNa4 or SKN5. Connection can be done by 8 tabs with quick connectors size 6.3 x 0.8mm

TECHNICAL DATA

Weight	23 gms
Rated Voltage	250 V
Rated Current	25 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Feed Through
Mounting Possibility	DIN 35/DIN 35-15 Rail

CONNECTION DATA

Conductor Cross Section Stranded min.	0.34 mm ²
Conductor Cross Section Stranded max.	6 mm ²

DIMENSIONS

Height with DIN 35 x 15 mm rail	61 mm
Height with DIN 35 x 7.5 mm rail	53.5 mm
Length	50 mm
Width (Thickness)	25.2 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CSTDE	6 sq.mm Diode Terminal Block with Heat Sink for Diode in Grey colour	10

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA509/K8	Marking Tag with Vertical printing.	100
	CSSTPC	Protective Cover	10

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	SPCSST2	partition plate in grey color	50
	SPCSST4	Protective Cover Holding Plate	50
	MC8	MARKER CARD 8MM PITCH WITH 48 TAGS	10

NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

CSTDE



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	IEC 60947-7-1		
Approvals	CE		
Conductor Cross Section Stranded min.	0.34 mm ²		
Conductor Cross Section Stranded max.	6 mm ²		
Rated Voltage	250 V		
Rated Current	25 A		