


CSTDE2



6 sq.mm Tab Connection Diode Terminal Block

CSTDE2 Terminal blocks are preferred for applications where the connections are subjected to severe vibrations.

These Terminal Blocks are suitable for solder diodes type SKN2.5 or SKNa2.

Connections can be done by 4 tabs with quick connectors size 6.3 x 0.8mm

TECHNICAL DATA

Rated Voltage	500 V
Rated Current	25 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	With Electronic Components: Diode/Resistor
Wire Entry Orientation	Side
Mounting Possibility	DIN 35/DIN 35-15 Rail

CONNECTION DATA

Conductor Cross Section Solid min	0.34 mm ²
Conductor Cross Section Solid max	6 mm ²

DIMENSIONS

Height	49 mm
Height with DIN 35 x 15 mm rail	59.5 mm
Height with DIN 35 x 7.5 mm rail	52 mm
Length	54 mm
Width (Thickness)	14 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CSTDE2	6 sq.mm Tab Connection Diode Terminal Block in Grey Colour	10

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	SPCSST2	partition plate in grey color	50


ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	SPCSST4	Protective Cover Holding Plate	50
	CA509/K10	Marking Tag Blank suitable for CTS10U / CGT10U / CGT10N / CHV10U / CTS10USC / STH4 / STH4DT / STH4DTSH / CSC10T Terminal Blocks	100
	MC10	MARKER CARD 10MM PITCH WITH 42 TAGS	10

NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

CSTDE2



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	IEC 60947-7-1		
Approvals	CE		
Conductor Cross Section Stranded min.	0.34 mm ²		
Conductor Cross Section Stranded max.	6 mm ²		
Rated Voltage	500 V		
Rated Current	25 A		