

CSR2S-230UYA-SN



SLIM RELAY MODULE 2CO 230VAC/VDC

- Compact & thin design
- Variety of Operating Voltages.
- High switching current : up to 8A at 24VDC/230VDC
- low coil power consumption.
- LED Indication on Coil activation.
- No requirement on polarity of input voltage
- Possibility of Jumpering Multiple slim relays together

TECHNICAL DATA

Bussing Possibility	Yes, By using shorting link
Supply Voltage Indication	Green LED
Ambient Operating Temperature	-40 to +55 °C
Mounting Possibility	DIN 35/DIN 35-15 Rail
Housing Material	PA 6,6 (V0)
Housing Colour	Grey
Rated Input voltage	230 V
Input Polarity Protection	Rectifier

RELAY GENERAL SPECIFICATIONS

Relay Type	Electromechanical Relay
Relay Make / Manufacturer	Hongfa / HF115F/110-2ZS4BF
Insulation Resistance	1000 Mega Ohms @50VDC , 25Deg. C
Relay Approvals	UL, VDE

RELAY INPUT / COIL SPECIFICATIONS

Nominal Operating Voltage	230VAC V
Nominal Input Current	11mA A
Maximum Operating Voltage	253VAC V
Must Operate Voltage	138VAC V
Must Release Voltage	50VAC V
Nominal Input Power	1.26 W

RELAY OUTPUT/CONTACT SPECIFICATIONS

Contact Type	2CO-DPDT
Contact Material	AgNi
Contact Resistance	100 m ohms max
Rated Contact Current (Resistive Load)	8 A
Load Voltage Range	440 VAC, 300 VDC
Maximum Switching Power	2000 VA, 192W

CONNECTION SPECIFICATIONS

Type of Connection	Screw Connection
Wire Stripping Length	10 mm
Torque	0.4 Nm

CONNECTION SPECIFICATIONS

Torque	4.5 lb-in
Min. Wire Size - Stranded(mm2)	0.2 mm ²
Max. Wire Size - Stranded(mm2)	2.5 mm ²
Min. Wire Size - Stranded(AWG)	24 AWG
Max. Wire Size - Stranded(AWG)	12 AWG
Min. Wire Size - Solid	0.2 mm ²
Max. Wire Size - Solid	2.5 mm ²
Min. Wire Size - Solid(AWG)	24 AWG
Max. Wire Size - Solid(AWG)	12 AWG

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	NO. OF CHN.	DIM. DET.	STD. PACK
CSR2S-230UYA-SN	2 CO 230VUC 2 Channel Slim Relay Module With Inbuilt Snubber Protection to protect from Short term voltage spikes.	1	14 x 94.5 x 101 mm	10

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	SCS0.5/3	Electricians Screwdriver for slotted screws	10
	ECAP 35/7.5	End Cap in Polyamide suitable for Din 35/7.5 rails	100
	ECAP 35/15	End Cap in Polyamide suitable for Din 35-15 rails	100

CSR2S-
230UYA-SN




connectwell
THE RIGHT CONNECTION

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	25
	IMACC/MR2S/110	2CO 110VDC MODULAR RELAY	100
	JX1.5/14/2	2 WAY SHORTING LNK FOR Slim Relay 2CO Coil Side	50
	JX1.5/14/3	3 WAY SHORTING LNK FOR Slim Relay 2CO Coil Side	50
	JX1.5/14/4	4 WAY SHORTING LNK FOR Slim Relay 2CO Coil Side	50
	JX1.5/7/4	4 WAY SHORTING LNK FOR Slim Relay 2CO Contact Side	50
	JX1.5/7/6	6 WAY SHORTING LNK FOR Slim Relay 2CO Contact Side	50
	JX1.5/7/8	8 WAY SHORTING LNK FOR Slim Relay 2CO Contact Side	50

CIRCUIT DIAGRAM



NOTES

Protection Degree:IP20
Pollution Degree:2
Over voltage / Surge voltage category-III
Relay operating time ≤ 15 (msec)
Relay release time ≤ 8(msec)

Dielectric Strength:
1)Between contacts and coil- 5kV AC (50Hz, 1min)
2)Between contact sets- 2.5kV AC(50Hz, 1min)
3)Between open contacts-1kV AC(50Hz, 1min)
4)Between Live parts /DIN rail-2kV AC (50Hz, 1min)

Insulation resistance: 1000M ohm @ 500VDC

Connection wires/ Conductors: 60/75 degC Copper conductor

PRODUCT DRAWING

