

CM4S2LF



4 sq. mm spring clamp terminal block with mounting feet.

A perfect solution for extremely compact wiring applications, these terminal block are modular and can be stacked to form multi-pole terminal block assemblies. CMLF series terminal Block have a side wire entry configuration.

TECHNICAL DATA

Rated Voltage	630 V
Rated Current	32 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Feed Through
Wire Entry Orientation	Side
Mounting Possibility	DIN 35/DIN 35-15 Rail
Rated Surge Voltage	6 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	4 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	10 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	0.2 mm ²
Conductor Cross Section Stranded with Ferrule/Lug max	1.5 mm ²
2 Conductors with same Cross Section Stranded min	0.2 mm ²
2 Conductor with same Cross Section Stranded max	1.5 mm ²
Conductor Cross Section Solid min	0.2 mm ²
Conductor Cross Section Solid max	4 mm ²
Stripping Length	10 mm

DIMENSIONS

Height	23 mm
Length	33.7 mm
Width (Thickness)	12 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CM4S2LF	4 sqmm spring clamp terminal block with mounting feet in grey colour	50
CM4S2LFYG	4 sqmm spring clamp terminal block with mounting feet Yellow-Green colour	50

NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

CM4S2LF



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	IEC/EN60947-7-1	UL 1059
Conductor Cross Section Stranded min.	0.2 mm ²	24 AWG
Conductor Cross Section Stranded max.	4 mm ²	10 AWG
Rated Voltage	630 V	300 V
Rated Current	32 A	26 A