



# **FLEXIBUS**

FLEXIBLE BUSBARS







## Introduction


Salzer group is India's leading manufacturer of low voltage switch gear products with international presence. Salzer has five world class manufacturing facilities with ISO 9001, ISO 14001and ISO 18001 accreditation. The group has a diverse product profile ranging from Cam Switches, Load Brake Switches, Wiring Ducts, Terminal blocks, Toroidal transformers, Modular switches, Wires & cables, Enamelled wires etc.,

#### Overview

Salzer flexibus are manufactured to international standards such as IEC, UL and CE. Salzer offers extensive range of flexibus to suit any industry for any known application.

Salzer flexibus are manufactured from 99.997% pure ETP grade annealed bare / tinned copper strips. Salzer has formulated special grade of insulation compound to give better flexibility and also meet flammability rating of UL 94VO and also RoHS Compliant. Salzer draw its strength and quality from the state-of-the art manufacturing facilities.

#### Features



## **Applications**



Panel Boards UPS / Stabilizers





Windmill



## Technical details

PRODUCT GROUP	FLEXIBUS	
Conductor		
Material	E-Cu 99.9 (standard) / E-Cu tinned (optional)	
Strip thickness	1mm	
Hardness	65 VPN	
Insulation		
Material	Special high flexible PVC	
Flammability	UL 94 VO	
Color	Black (other colors optional)	
Thickness	≥ 1.6 mm	
Dielectric strength	20 kV/mm	
Elongation	min. 150%	
Tensile Strength	min. 10.3 N m	
Operating temperature	- 20 to + 105 °C	
Operating voltage	750 V AC / 1000 V AC	
Dimensions		
Length	2000 / 3000 mm (standard)	
Width	20 - 100 mm	
Appovals	. <b>₽1</b> (€	

## Dimensions

Nominal current carrying capacity	Dimensions (width x number of strips x thickness) Cu bare (mm)	Cross Section
250A	20x2x1	40.0
	20x3x1	60.0
	20x4x1	80.0
	24x2x1	48.0
	24x3x1	72.0
	32x2x1	64.0
	20x5x1	100
	20x6x1	120
400A	24x4x1	96
	24x5x1	120
	32x3x1	96
500A	24x6x1	144
	32x4x1	128
630A	20x10x1	200
	24x8x1	192
	24x10x1	240
	32x5x1	160
	32x6x1	192
	40x5x1	200
	32x8x1	256
	32x10x1	320
	40x8x1	320
	50x5x1	250

Nominal current carrying capacity	Dimensions (width x number of strips x thickness) Cu bare (mm)	Cross Section
1000A	40x10x1	400
	50x8x1	400
	63x5x1	315
1250A	63x6x1	378
	63x8x1	504
	80x4x1	320
	80x5x1	400
	80x6x1	480
1600A	80x8x1	640
	100x6x1	600
2000A	100x8x1	800





## Custom made

















Cutting Bending Twisting Hole pattern Oblong holes

FLEXIBUS - custom made designs according to the requirements



SALZER Electronics Ltd, Unit-II Chinnamadampalayam, Coimbatore - 641019. India. Phone : +91 4254 302000 Fax : +91 4254 272012. E-mail: salzer2@salzergroup.com Visit us at: www.salzergroup.com